

## SafeSeal

### Description:

- For enhanced water security
- SafeSeal will prevent moisture from penetrating down into the joints
- Specially developed for areas requiring extra moisture protection
- One bottle is enough for approx 20 m<sup>2</sup> flooring.



### Characteristics:

Properties	
Binder	PVAc dispersion
Classification	D3 (EN 204)
Colour	White, transparent when dry
Bottle	0,5 litre, enough for approx 20m <sup>2</sup>
Temperature	Used at a temperature of at least 15° C

Other	
Cleaning	Wipe off using a damp cloth (water), or peel off after drying 10-15 minutes (skin dry)
Shelf life	12 months in unopened package
Storage	Store cool and frost free between +5 °C and +25 °C.

Product	Contain
SafeSeal, 45050	1 pcs

### Instructions:

Clean and brush the flooring panel from all loose particles

#### To be used as sealing:

Apply a thin line of SafeSeal on the top of the tongue on the longside of the plank only before assembling.

Wipe off excess SafeSeal using a damp cloth (water), or peel off after drying 10-15 minutes (skin dry). On floors with bevelled edge, the excess SafeSeal must be wiped off directly.

#### To be used for bigger area of installation:

Apply a thin line of SafeSeal in the bottom of the longside groove on the already installed plank.

